

## UNITED STATES PATENT AND TRADEMARK OFFICE

DATE MAILED: 05/07/2002

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
08 952,996	04/10/1998	MATS LEIJON	70559-2 8241	3267
25269	7590 05 07/2002			
DYKEMA GOSSETT PLLC FRANKLIN SQUARE, THIRD FLOOR WEST 1300 I STREET, NW			EXAMINER	
			MULLINS, BURTON S	
WASHINGTON, DC 20005			ART UNIT	PAPER NUMBER
			2834	

Please find below and/or attached an Office communication concerning this application or proceeding.

	· · · · · · · · · · · · · · · · · · ·	Application No.	Applicant(s)			
,	Office Action Summary	08/952,996	LEIJON ET AL.			
	Office Action Summary	Examiner	Art Unit			
	The MAN INC DATE of this communication on	Burton S. Mullins	2834			
Period fo	The MAILING DATE of this communication ap or Reply	pears on the cover sheet with the	ne correspondence address			
THE - Exte after - if the - if NC - Failu - Any	ORTENED STATUTORY PERIOD FOR REPIMALING DATE OF THIS COMMUNICATION risions of time may be available under the provisions of 37 CFR 1 SIX (6) MONTHS from the mailing date of this communication. Period for reply specified above is less than thirty (30) days, a reperiod for reply is specified above, the maximum statutory period reto reply within the set or extended period for reply will, by statuely received by the Office later than three months after the mailing days and the property of the maximum statutory period reply received by the Office later than three months after the mailing days and the property of the maximum statutory period for reply will, by statuely received by the Office later than three months after the mailing days and the provided period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply within the set of extended period for reply will be set to reply wil	.136(a). In no event, however, may a reply b ply within the statutory minimum of thirty (30 d will apply and will expire SIX (6) MONTHS te, cause the application to become ABAND	pe timely filed ) days will be considered timely. from the mailing date of this communication. ONED (35 U.S.C. § 133).			
1)⊠	Responsive to communication(s) filed on <u>08</u>	March 2002				
2a)☑	This action is <b>FINAL</b> . 2b) T	his action is non-final.				
3) Dispositi	3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.  Disposition of Claims					
4)[	Claim(s) 1-29 and 31-44 is/are pending in th	e application.				
	4a) Of the above claim(s) is/are withdra	awn from consideration.				
5)	5) Claim(s) is/are allowed.					
6) 🖂	6)☑ Claim(s) <u>1-29 and 31-44</u> is/are rejected.					
7)	7) Claim(s) is/are objected to.					
8)	8) Claim(s) are subject to restriction and/or election requirement.					
1	on Papers	,				
9) 🗌 .	The specification is objected to by the Examin	er.				
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
11) The proposed drawing correction filed on is: a) ☐ approved b) ☐ disapproved by the Examiner.						
	If approved, corrected drawings are required in re	eply to this Office action.				
12) 🗌	The oath or declaration is objected to by the E	xaminer.				
Priority ι	ınder 35 U.S.C. §§ 119 and 120					
13)	Acknowledgment is made of a claim for foreig	gn priority under 35 U.S.C. § 11	9(a)-(d) or (f).			
a)[	a) ☐ All b) ☐ Some * c) ☐ None of:					
	1. Certified copies of the priority documents have been received.					
	2. Certified copies of the priority documents have been received in Application No					
<ul> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
14) 🗌 A	cknowledgment is made of a claim for domes	tic priority under 35 U.S.C. § 1	19(e) (to a provisional application).			
	The translation of the foreign language particles. The translation of the foreign language particles.	•	120 and/or 121.			
Attachmen	(s)		BUHTUIN O MULLINS			
2) Notic 3) Inform	e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (PTO-948) nation Disclosure Statement(s) (PTO-1449) Paper No(s)	5) Notice of Inform	mary (PTO-413) Paper No(s). EXAMINER mal Patent Application (PTO-152)			
US Patent and To PTO-326 (Re		Action Summary	Part of Paper No. 35			

Application/Control Number: 08/952,996

Art Unit: 2834

## **DETAILED ACTION**

## Claim Rejections - 35 USC § 103

- 1. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
- 2. Claims 1-9,11,15-29,31 and 32 are rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's disclosed Prior Art Figure 3 in view of Shildneck (USP 3,014,139) and further in view of Elton et al. (USP 5,036,165). Prior art figure 3 discloses the claimed invention except for having a winding comprising of an insulation system and at least two semiconducting layers, the layers having substantially the same coefficient of thermal expansion. Shildneck teaches that it is known to use a cable winding in a dynamo-electric machine. Shildneck discloses an improved continuous winding for an electromagnetic device such as a large turbine-driven generator, the winding employing an improved form of flexible insulated conductor for the laminated armature core of the dynamo-electric machine. In addition, Elton et al. teach that it is known to have an electrical cable comprising an internal grading layer of semi-conducting pyrolyzed glass fiber layer in electrical contact with the cable conductor. In another form of embodiment, Elton et al. teach an electrical cable provided with an exterior layer of internal grading layer of semi-conducting pyrolyzed glass fiber layer in contact with an exterior cable insulator with a predetermined reference potential.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have used the cable assembly of Shildneck having semiconducting layers as taught by Elton et al. to the device as disclosed in prior art figure 3 since such a

Page 3

Application/Control Number: 08/952,996

Art Unit: 2834

modification according to Elton et al. would provide a conductor which prohibits the development of corona discharge.

In regard to forming the semiconducting layer with the same coefficient of thermal expansion as that of the insulation layer, it would have been obvious to one having ordinary skill in the art at the time the invention was made to have formed these layers with similar coefficients since it was known in the art that the expansion rate of the two layers would be the same and this is desirable in order to prevent cracking of the insulation and wear between the two.

3. Claims 10 and 33-44 are rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's disclosed prior art Figure 3 in view of Shildneck (USP 3,014,139) and Elton et al. (USP 5,036,165) and further in view of Takaoka et al. (USP 5,094,703). Prior art figure 3, Shildneck and Elton et al. disclose the claimed invention except for a teaching of having the strands of the electrical conductor comprised of insulated and uninsulated windings.

Takaoka et al., as seen in figures 7,8,10 and 11 teach having a stranded conductor for an electrical cable comprising a combination of uninsulated stranded conductor and an insulated stranded conductor.

It would have been obvious to one having ordinary skill in the art at the time the invention was made to have used the teaching of Takaoka et al. having insulated and uninsulated electrical conductor strands and to have modified the device of Elton et al. since such a modification would reduce the amount of insulation needed minimizing assembly and production costs.

Page 4

Application/Control Number: 08/952,996

Art Unit: 2834

4. Claim 12 is rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's disclosed prior art Figure 3 in view of Shildneck (USP 3,014,139) and Elton et al. (USP 5,036,165) and further in view of Breitenbach et al. (USP 4,785,138). Prior art figure 3 and Elton et al. disclose the claimed invention except for a teaching of having metal screen and sheath in the cable.

Breitenbach et al. teach that it is known to utilize metal screen and sheath in the cable. It would have been obvious to one having ordinary skill in the art at the time the invention was made to used the arrangement of Breitenbach et al. to the device of as disclosed by Elton et al. since such a modification according to Breitenbach et al. in column 4, lines 59-69 would provide mechanical protection and electrical shield for the cable.

5. Claims 13 and 14 are rejected under 35 U.S.C. § 103(a) as being unpatentable over Applicant's disclosed prior art Figure 3 in view of Shildneck (USP 3,014,139) and Elton et al. (USP 5,036,165) and further in view Lauw (USP 4,982,147). Prior art figure 3 and Elton et al. disclose the claimed invention except for a teaching of having or not having a step-up transformer in the system device.

Lauw in column 6, lines 50-52 teach that use of transformers to step-up or step down the voltage are contingent upon the requirements of the application. In this instant application, having a voltage higher than 30kV-36kV, it would have been an obvious matter of design choice to one having ordinary skill in the art to utilize a step-up transformer in order to increase and meet the required voltage in the application.

Page 5

Application/Control Number: 08/952,996

Art Unit: 2834

6. Applicant's arguments filed 3-8-02have been fully considered but they are not persuasive. Applicant provided various arguments as to why the combination of the referenced prior arts were not obvious, since the references fail to teach or suggest motivations for combining. Applicant asserts that Elton (` 165) disclose only a transmission and distribution cable and that Elton et al. (`565), the parent application which was incorporated by reference, disclose generally the use of semi-conducting layer for insulated electrical conductors in three distinct embodiments.

Moreover, applicant argues that in Elton et al. (`565) the conductors of the dynamoelectric machine are referred to exclusively as "windings" or "bars", and when referring to an electrical cable for carrying high voltage, Elton et al. (`565) refer to the conductors as "cable" not a "winding" or "bar". Applicant concludes that when the disclosure is taken together, the conductor designated in Elton et al. (`165) relates to an electrical cable for transmission and distribution of electrical power and not for a winding for a dynamo electric machine. Applicant further argues that these are separate applications utilizing a common component and that Elton et al. (1'65 and `565) do not teach the cable and the winding to be interchangeable.

Examiner disagrees with applicant's argument and contends that Elton et al. (` 165) provide a teaching or suggestion for using his cable arrangement having semi-conducting layers for dynamo-electric machines applications.

It is important to note that the thrust of the invention of Elton et al. (` 165 and `565) is the use of a semi-conducting layer material with an insulated conductor. In addition, Elton et al. (`565) in column 8, lines 14-25, clearly suggest that while the embodiments or examples

Application/Control Number: 08/952,996 Page 6

Art Unit: 2834

illustrate only electrically grounded insulation bodies in combination with the semi-conducting layer, any one having ordinary skill in the art will appreciate that "any body having a known electric potential may be coupled to the semi-conducting layer to eliminate the effects of ambient electrical fields or charges developed within or without the electrical conductor or encompassed components."

Elton et al. (`565) provided three distinct embodiments utilizing a semiconducting layer, namely, in windings of a dynamoelectric machine, electrical cables and electrical housing surrounding a digital electronic equipment. In all applications, Elton et al (`565) teach that when the semiconducting layer is in electrical contact with an electrical ground, the layer prohibits the development of a corona discharge and bleeds off any electric charge developed on the exterior surface of an insulated conductor, (see column 7 lines 64 through column 8, lines 1-25).

In the art of motors, and as recognized by Elton et al. (` 165), the problem of corona discharge in dynamo electric machines is commonly known and ever present. Elton et al. (` 165) describes this problem in the background of the invention (column 1, lines 15-35) that corona discharge develops whenever an electrical potential exists between the conductor and the region adjacent the exterior surface of the insulator. The stationary armature core are generally made of laminations which define circumferentially spaced radial slots opening into the bore. Disposed in the slots are heavily insulated electrical windings causing a high electrical potential to exists between the windings or armature bars and the members of the stator defining the slots which are at an electrical ground. Accordingly, when the

Application/Control Number: 08/952,996

Art Unit: 2834

development of corona discharge and bleeds off any electric charge developed on the exterior surface of an insulated conductor.

Since other variations of dynamoelectric machines designed for high voltage applications such as Siemens and Shildneck utilize rounded cables for its windings in the stator core slots, why would one skilled in the art not use the semiconducting layers and modify the existing cable? Or why would one skilled in the art not utilize a cable similar to the one disclosed by Elton et al.?

It is noted that Elton et al. (` 165) in column 2, lines 48-52 also teach the number of semiconducting layers applied may vary depending on the design requirements.

Moreover, applicant's argument limiting the use of the electrical "cable" for electrical transmission and distribution only is not well understood. As defined by Webster's II New Riverside University dictionary, a cable is "a bound or sheathed group of mutually insulated conductors". The windings in the dynamoelectric machine, including those for high voltage applications, use these type of conductors for electrical transmission.

Examiner disagrees with applicant's argument that the cable of Elton et al. (`565) is stiff due to the presence of the semiconducting layer made of pyrolized glass layer. The rigidity of a conductor cable primarily depends on the type of insulation used. Shildneck for instance, in column 2, lines 28-30 teaches that the rigidity of the conductor bars depend on the type of insulation used. Shildneck uses silicone-rubber insulation in his flexible cable.

Moreover, as is known in power cables, cable flexibility primary depends upon the use of ethylene-propylene (EPM) and ethylene-propylene-dime (EPDM) rubbers as insulation rather than of the semiconducting layer.

Application/Control Number: 08/952,996

Art Unit: 2834

Elton et al. (` 565) in column 8, lines 3-9, teach that the semi-conducting pyrolized glass layer can be chopped, mixed with resin and molded or blown on any complex shaped substrate so that the layer can be placed in intimate contact with substantially all of the exterior surface of the insulator or housing. As such, the semi-conducting layer does not cause cable rigidity.

## Conclusion

7. This is a RCE of applicant's earlier Application No. 08/952,996. All claims are drawn to the same invention claimed in the earlier application and could have been finally rejected on the grounds and art of record in the next Office action if they had been entered in the earlier application. Accordingly, **THIS ACTION IS MADE FINAL** even though it is a first action in this case. See MPEP § 706.07(b). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no, however, event will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Application/Control Number: 08/952,996 Page 9 Art Unit: 2834 Any inquiry concerning this communication or earlier communications from the 8. examiner should be directed to Burton S. Mullins whose telephone number is 305-7063. The examiner can normally be reached on Monday-Friday, 9 am to 5 pm. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nestor Ramirez can be reached on 308-1371. The fax phone numbers for the organization where this application or proceeding is assigned are 305-1341 for regular communications and 305-1341 for After Final communications. Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 308-0956. **Primary Examiner** Art Unit 2834

bsm

May 6, 2002